Hunan Standard Steel Co., Ltd

Bond Strength

50°C±5°C

≥15 N/cm

≥50 N/cm

≥50 N/cm

≥50 N/cm

20°C±5°C

≥90 N/cm

≥90 N/cm

≥90 N/cm

THE REQUIREMENTS OF ABOVE SPECIFICATIONS AND PURCHASE ORDER, AND MEET THE REQUIREMENTS.

WE HEREBY CERTIFY THAT THE MATERIAL HEREIN DESCRIBED HAS BEEN MANUFACTURED AND INSPECTED IN ACCORDANCE WITH

≥35 N/cm

Percentage

elongation at

failure

> 200%

> 200%

> 200%

≥200%

Impact

Strength

≥5 J/mm

> 8 J/mm

> 8 J/mm

> 8 J/mm

Continuity

25KV

25KV

25KV

25KV

Indentation Hardness

50°C±2°C

< 0.3 mm

< 0.3 mm

< 0.3 mm

≤0.3mm

23°C±2°C

< 0.2 mm

< 0.2 mm

< 0.2 mm

≤0.2mm

		Mill Test	Certificate		
Description of Goods	S ERW STEEL PIPES		Contract No:	HSCO20160815	
Standard:	DIN 30 670		Issue Date:	2016/9/21	
				,	
			Inspection Item		

Blasting Grade

Sa2.5

Sa2.5

Sa2.5

Sa2.5

Quantity

Length(M)

8579.9

23252.6

5688.2

Piece

721

1954

478

Serial

No.

2

SURVEYOR

Technical Standard

Specification

88.9*3.2*11900

273.1*5.6*11900

273.1*6.4*11900

Coating Film

Thickness

mm

 ≥ 1.8

 ≥ 2.0

 ≥ 2.0